

ExamsNest

Your Ultimate Exam Preparation Hub

Vendor: Arista
Code: ACE-A1.2

Exam: Arista Certified Engineering Associate https://www.examsnest.com/exam/ace-a12/

QUESTIONS & ANSWERS

DEMO VERSION

QUESTIONS & ANSWERS DEMO VERSION (LIMITED CONTENT)

Version: 9.0

VCISIOIII SIO	
Question: 1	
On EOS 4.13.1F, which of the following statements are true in regards feature? (Select two)	s to Arista's Tap Aggregation
A. Tap ports are send only.B. Tap ports are receive only.C. Tool ports are send only.D. Tool ports are receive only.	
- -	Answer: A,D
Question: 2	
Where does Aboot look for the boot system image at boot time?	
A. At the location specified in the running-configB. At the location specified in the startup-configC. At the location specified in a file named boot-config on flash:D. At the location specified in a file named boot_config on flash:	
·	Answer: C
Question: 3	
When ZTP is in enable node, what triggers ZTP when the switch boots?	
A. A missing or zero-byte SWI image.B. A missing or zero-clue administrator.C. A missing or zero-byte startup-config fileD. A missing or zero-byte running-config file	
	Answer: C
Question: 4	
Which of the following are valid Event Manager triggers?	

Which of the following are valid Event Manager triggers?

- A. on-boot
- B. on-schedule
- C. on-startup-config
- D. on-reload

	Answer: A,C
Question: 5	
Which of the following Arista switch series' supports Zero Touch Provision	oning (ZTP)?
A. 7050	
B. 7280E	
C. 7300	
D. 7500E	
	Answer: D
Question: 6	
Which command would you use to change the SSH Idle timeout after e command?	ntering the 'management ssh'
A. idle-timeout <minutes></minutes>	
B. timed <minutes> C. timeout <minutes></minutes></minutes>	
D. ssh-idle <minutes></minutes>	
2. 331 fale similates	
	Answer: A
Question: 7	
What would be the result of issuing a reload command on one of the in an MLAG domain where both switches are running EOS version 4.14.	•
A. Dual-homed hosts lose 50% of network capacity through the ML reboots	AG domain while the switch
B. The peer switch also reboots to ensure network stability.	
C. The peer switch sends out gratuitous BPDUs to let the network know	that it has assumed the root-
bridge role.	
D. Nothing bad ever happens when MLAG is enabled!	
	Answer: A
Question: 8	

On an Arista switch, which port is used to connect a laptop to the switch for initial configuration or password recovery?

- A. Ethernet 1
- B. Console

Answer: B

C. Management 1 D. Ethernet 1/1	
	Answer: A
Question: 9	
How many Arista switches may be a part of a single MLAG domain?	
A. 2 B. 4 C. 8 D. 16	
	Answer: A
Question: 10	
Which of the following are not valid boot-config file entries?	
A. NETGW=192.168.1.1 B. IMAGE-flash:EOS-4.12.1.swi C. SWI=flash:EOS-4.12.1.swi D. SWIX=flash:EOS-4.12.1.swi	



Thank You for trying the PDF Demo

Vendor: Arista
Code: ACE-A1.2

Exam: Arista Certified Engineering Associate https://www.examsnest.com/exam/ace-a12/

Use Coupon "SAVE15" for extra 15% discount on the purchase of Practice Test Software. Test your Exam preparation with actual exam questions.

Start Your Preparation