

ExamsNest

Your Ultimate Exam Preparation Hub

Vendor: Esri
Code: EADP19-001

Exam: ArcGIS Desktop Professional 19-001 https://www.examsnest.com/exam/eadp19-001/

QUESTIONS & ANSWERS

DEMO VERSION

QUESTIONS & ANSWERS DEMO VERSION (LIMITED CONTENT)

Version: 4.0

Overtion 1
Question: 1
An ArcGIS user is making a map showing the standard deviation from the mean ocean temperature. Which type of color ramp should be used to display the standard deviation?
A. a three-color multipart color ramp B. a two-color algorithmic color ramp C. a random color ramp
D. a thirteen-color preset color ramp
Answer: B
Explanation:
Question: 2
An ArcGIS user is given a geodatabase and tasked with adding a feature class to an existing geodatabase topology. What should the user do?
A. delete the existing geodatabase topology and create a new one to include the feature class B. modify the existing geodatabase topology to include the feature class Explanation:-https://desktop.arcgisxom/en/arcmap/10.3/tools/data-m
C. export the existing geodatabase topology to an XML file include the feature class in the XML and import it
D. remove all the feature classes from existing topology and add everything back including the feature class that needs to be added
Answer: B
Explanation:
Question: 3

Data in the state of Louisiana has the projection defined as WGS 1984 UTM Zone 15S. The user knows that this area of Louisiana is located m UTM Row S. When added to ArcMap with other data that draws in the correct location the data with the Zone 15S definition draws in the vicinity of the North Pole.

What is wrong with the projection definition?

- A. The "S" indicates south of the equator instead of UTM Row S
- B. The false northing value should be 0. not 10000000
- C. The latitude of origin should be -80 degrees, not 0

Explanation:

D. The units should be feet instead of meters	
	Answer: A
Explanation:	
Question: 4	
An ArcGIS user has a project that requires using an image with a spat Mean Square Error (RMSE) or better. How should users verify the spatial accuracy of the image? A. They should verify that the image resolution is less than 5 meters	ial accuracy of 5 meters Root
B. They should compare the image to surveyed control points of high ac C. They should visually inspect the image to make sure there are r compromise the sp accuracy D. They should compute an RMSE and compare the results to the result	no obvious errors that would
	Answer: B
Explanation:	
Question: 5	
An ArcGIS user has a custom .dll that reads the domains available in them to business rules. What must the user do to have this tool run aut	-
An ArcGIS user has a custom .dll that reads the domains available in them to business rules. What must the user do to have this tool run aut A. add the dll to a model and schedule the model through the Windows B. create a stand-alone application to publish a service and schedule Windows Task Scheduler	omatically each night? Task Scheduler the application through the
An ArcGIS user has a custom .dll that reads the domains available in them to business rules. What must the user do to have this tool run aut A. add the dll to a model and schedule the model through the Windows B. create a stand-alone application to publish a service and schedule	omatically each night? Task Scheduler the application through the Windows Task Scheduler



Thank You for trying the PDF Demo

Vendor: Esri
Code: EADP19-001

Exam: ArcGIS Desktop Professional 19-001 https://www.examsnest.com/exam/eadp19-001/

Use Coupon "SAVE15" for extra 15% discount on the purchase of Practice Test Software. Test your Exam preparation with actual exam questions.

Start Your Preparation