



ExamsNest

Your Ultimate Exam Preparation Hub

ExamsNest

Your Ultimate Exam Preparation Hub

Vendor: Fortinet

Code: FCP_FMG_AD-7.6

Exam: FCP - FortiManager 7.6 Administrator

https://www.examsnest.com/exam/fcp_fmg_ad-76/

QUESTIONS & ANSWERS

DEMO VERSION

QUESTIONS & ANSWERS
DEMO VERSION
(LIMITED CONTENT)

Version: 4.0

Question: 1

You want to let multiple administrators work in the same ADOM without creating configuration conflicts.

What is the best and the most effective solution to apply?

- A. Configure RADIUS authentication to assign ADOM roles to each user.
- B. Enable workflow mode, which is the only way to prevent concurrent configuration conflicts.
- C. Assign administrators with JSON API access to the FortiManager.
- D. Activate workspace mode in the ADOM settings.

Answer: D

Explanation:

Activating workspace mode in the ADOM settings allows multiple administrators to work concurrently in the same ADOM by isolating their configuration changes in separate workspaces, preventing conflicts and enabling effective collaboration.

Question: 2

Refer to the exhibit.

FortiManager cluster settings

FortiManager

Cluster Settings

Failover Mode: **Manual** **VRRP**

Operation Mode: **Standalone** Primary Secondary

Peer IP and Peer SN

IP Type	Peer IP	Peer SN	Action
IPv4	10.0.1.242	FMG-VM0A169	✕ +

Cluster ID: 1 (1-64)

Group Password:

File Quota: 4096 MB (2048-20480)

Heart Beat Interval: 10 Seconds

Failover Threshold: 30 (1-255)

VIP: 10.0.1.245

VRRP Interface: port2

Priority: 1 (1-253)

Unicast: ☐

Monitored IP

IP	Interface	Action
10.0.1.241	port2	✕ +

Download Debug Log [Download](#)

If the monitored interface for the primary FortiManager device fails, what must you do to maintain high availability (HA)?

- A. The FortiManager HA failover is transparent to administrators and does not require any additional action.
- B. Manually promote one of the working secondary devices to the primary role: and reboot the original primary device to remove the peer IP address of the failed device.
- C. Reconfigure the primary device to remove the peer IP address of the failed device from its configuration.
- D. Check the integrity database of the primary device to force a secondary device to become the new primary with all active interfaces.

Answer: A

Explanation:

In a FortiManager HA cluster configured with VRRP failover, the failover process is automatic and transparent to administrators. If the monitored interface on the primary device fails, the secondary device takes over without requiring manual intervention to maintain HA.

Question: 3

Refer to the exhibit.

FortiManager address object

Edit Address - LAN

Category

Address

Name

LAN

Color



Change

Type 

Subnet

IP/Netmask

 172.16.5.0/255.255.255.0

 Resolve from name

Interface

☐ any

Static Route Configuration

☒

Comments

0/255

Add To Groups

Click to select

Advanced Options >

Per-Device Mapping ▾

+ Create New

 Edit

 Delete

Search...  

☐	Mapped Device ⇅	Details ⇅ 
☐	BR1-FGT-1 [root]	IP/Netmask: 10.10.10.5/255.255.255.255
☐	HQ-NGFW-1 [root]	IP/Netmask: 172.16.5.20/255.255.255.255
☐	 Remote-Firewall [root]	IP/Netmask: 21.21.2.5/255.255.255.255

3

An administrator has created a firewall address object that is used in multiple policy packages for multiple FortiGate devices in an ADOM.

After the installation operation is performed, which IP/netmask will be installed on Remote-Firewall [VDOM1] for the LAN firewall address object?

- A. 21.21.2.5/255.255.255.255
- B. 172.16.5.20/255.255.255.255
- C. 172.16.5.0/255.255.255.0
- D. 10.10.10.5/255.255.255.255

Answer: A

Explanation:

The per-device mapping overrides the global IP/netmask setting for the firewall address object. For the device "Remote-Firewall," the mapped IP/netmask is 21.21.2.5/255.255.255.255, so this value will be installed on Remote-Firewall [VDOM1].

Question: 4

Refer to the exhibits.

Device Revision Diff wizard

Device Revision Diff

Revision ID: 11	
Total	12696
Deleted	0
Modified	0

```
8500 (...)
      end

8501 config user group
      (...)
12154 set service "ALL"
12155 set comments "test"
      (...)
```

Revision ID: 9

Total	12704
Added	8
Modified	0

```
8500 (...)
      end
8501 config user local
8502 edit "Support"
8503 set type password
8504 set two-factor email
8505 set email-to "support@mail.com"
8506 next
8507 end
8508 config user group
      (...)
12161 set service "ALL"
12162 set users "Support"
12163 set comments "test"
      (...)
```

Save Diff as Script

Show Full Diff

Cancel

CLI output

```
FortiManager # diagnose dvm device list
--- There are currently 6 devices/vdoms managed ---
--- There are currently 6 devices/vdoms count for license ---

TYPE      OID      SN              HA      IP      NAME      ADOM      IPS      FIRMWARE      HW_GenX
fmgfaz-managed 188      FGV082TN24013504 -      100.65.1.111 BR1-FGT-1  My_ADOM  7.0 MR6 (3401) N/A
|- STATUS: dev-db: not modified; conf: in sync; cond: OK; dm: installed; conn: up; template:[installed]default
|- vdom:[3]root flags:0 adom:My_ADOM pkg:[unknown]BR1-FGT-1
```

An administrator needed to recover all the configurations related to the user, Support. The configurations were saved in configuration revision ID 9.

The administrator reverted the configuration using the Configuration Revision History window and received the CLI output shown in the exhibit.

What can you conclude from the CLI output?

- A. The administrator set the flag to 0 to prevent configuration overrides.
- B. The administrator reinstalled the policy package.
- C. The administrator needs to retrieve the device to correctly detect the FortiGate firmware version.
- D. The administrator installed only the device-level configuration.

Answer: C

Explanation:

The CLI output shows the status "dev-db: not modified; conf: in sync; cond: OK; dm: installed," but the firmware version for the device is listed as "[unknown]." This indicates that FortiManager has not properly detected the FortiGate firmware version, likely because the device needs to be retrieved to update its information.

Question: 5

An administrator wants to configure and manage multiple objects in the FortiManager database and give access to other users who work in the same database.

To stay in control of the changes made to firewall policies by other team members, the administrator needs a setup where all modifications go through a central check before they can be installed.

How can the administrator create this setup?

- A. Enable the prompt asking the administrator to accept firewall policies changes before saving.
- B. Enable the workspace (for all ADOMs) to control all changes made by any administrator.
- C. Enable device lock and the advanced mode feature in the ADOM.
- D. Enable workflow mode and the ADOM lock feature.

Answer: D

Explanation:

Enabling workflow mode along with the ADOM lock feature ensures that all configuration changes go through a centralized review and approval process before installation, allowing controlled and

coordinated management of firewall policies by multiple administrators.



ExamsNest

Your Ultimate Exam Preparation Hub

Thank You for trying the PDF Demo

Vendor: Fortinet

Code: FCP_FMG_AD-7.6

Exam: FCP - FortiManager 7.6 Administrator

https://www.examsnest.com/exam/fcp_fmg_ad-76/

Use Coupon “**SAVE15**” for extra 15% discount on the purchase of Practice Test Software. Test your Exam preparation with actual exam questions.

Start Your Preparation