



ExamsNest

Your Ultimate Exam Preparation Hub

ExamsNest

Your Ultimate Exam Preparation Hub

Vendor: NetApp

Code: NS0-593

Exam: NetApp certified support engineer - ONTAP specialist

<https://www.examsnest.com/exam/ns0-593/>

QUESTIONS & ANSWERS

DEMO VERSION

QUESTIONS & ANSWERS
DEMO VERSION
(LIMITED CONTENT)

Version: 4.1

Question: 1

When you review performance data for a NetApp ONTAP cluster node, there are back-to-back (B2B) type consistency points (CPs) found occurring on the root aggregate.

In this scenario, how will performance of the client operations on the data aggregates be affected?

- A. During B2B processing, clients will be unable to write data.
- B. Data aggregates will not be affected by B2B processing on another aggregate.
- C. During B2B processing, all I/O to the node is stopped.
- D. During B2B processing, clients will be unable to read data.

Answer: B

Explanation:

A B2B type consistency point (CP) occurs when a new CP is triggered before the previous CP is completed, due to the second memory buffer reaching a watermark. This can cause write latency to increase as user write operations are not replied until a write buffer frees up. However, this only affects the aggregate that is undergoing the B2B processing, and not the other aggregates on the same node. Therefore, the performance of the client operations on the data aggregates will not be affected by B2B processing on the root aggregate. Reference = [What is the Back-to-Back \(B2B\) Consistency Point Scenario?](#), [What are the different Consistency Point types and how are they measured in ONTAP 9?](#), [What are the different Consistency Point types and how are they measured?](#)

Question: 2

Recently, a CIFS SVM was deployed and is working. The customer wants to use the Dynamic DNS (DDNS) capability available in NetApp ONTAP to easily advertise both data UFs to their clients. Currently, DNS is only responding with one data LIF. DDNS is enabled on the domain controllers.

```
vservers      lif      data-protocol is-dns-update-enabled
-----
svm1          cifs_01 nfs,cifs      true
svm1          cifs_02 cifs        true
svm1          mgmt    none          false
3 entries were displayed.
```

```
cluster1::*> vservers services dns dynamic-update show
Vservers      Is-Enabled Use-Secure Vservers FQDN      TTL
-----
svm1          false      false      svm1.demo.net    24h
```

Referring to the exhibit, which two actions should be performed to enable DDNS updates to work? (Choose two.)

<https://www.examsnest.com>

- A. Disable the -vserver-fqdn parameter for the SVM DDNS services.
- B. Remove the NFS protocol from the cifs_01 data LIF.
- C. Enable the -use-secure parameter for the SVM DDNS services.
- D. Enable the -is-enabled parameter for the SVM DDNS services

Answer: B, D

Explanation:

To enable DDNS updates to work, two actions should be performed:

Remove the NFS protocol from the cifs_01 data LIF. [This is because DDNS updates are only supported for LIFs that have only one data protocol enabled1](#). The cifs_01 LIF has both NFS and CIFS protocols enabled, which prevents it from registering its DNS record dynamically. By removing the NFS protocol from the cifs_01 LIF, it will become eligible for DDNS updates.

Enable the -is-enabled parameter for the SVM DDNS services. [This is because the -is-enabled parameter controls whether the SVM sends DDNS updates to the DNS servers2](#). The exhibit shows that the -is-enabled parameter is set to false for the svm1 SVM, which means that it does not send any DDNS updates. By enabling the -is-enabled parameter, the SVM will start sending DDNS updates for its eligible LIFs. Reference:

[1: Configure dynamic DNS services3](#)

[2: Manage DNS/DDNS services with System Manager4](#)

Question: 3

A customer is calling you to troubleshoot why users are unable to connect to their CIFS SVM.

```
ClusterB::*> storage disk show -broken
```

```
Original Owner: Node03
```

```
Checksum Compatibility: block
```

Physical		Disk		Outage Reason		HA Shelf Bay /Slot	Drawer	Usable
Chan	Pool	Type	RPM	Size	Size			
1.0.2	failed	3b	0	2	-/-	B		
FAILED	BSAS	7200	1.62TB	1.62TB				

```
ClusterB::*> cluster ring show
```

Node	UnitName	Epoch	DB Epoch	DB Trnxs	Master	Online
Node03	mgmt	11	11	4875	Node04	secondary
Node03	vldb	0	11	358	-	offline
Node03	vifmgr	11	11	4892	Node04	secondary
Node03	bcomd	11	11	62	Node04	secondary
Node03	crs	11	11	6	Node04	secondary
Node04	mgmt	11	11	4875	Node04	master
Node04	vldb	0	11	358	-	offline
Node04	vifmgr	11	11	4892	Node04	master
Node04	bcomd	11	11	62	Node04	master
Node04	crs	11	11	6	Node04	master

10 entries were displayed.

```
ClusterB::*> system node run -node Node04 -command aggr status -r aggr2
```

```
Aggregate aggr2 (online, raid_dp, degraded) (block checksums)
```

```
Plex /aggr2/plex0 (online, normal, active, pool0)
```

```
RAID group /aggr2/plex0/rg0 (degraded, block checksums)
```

RAID Disk Device	HA	SHELF	BAY	CHAN	Pool	Type	RPM	Used (MB/blks)	Phys
Opacity	FAILED							2538546/ -	
parity	3c.0.11	3c	0	11	SA:B	0	BSAS	7200	2538546/5198943744
data	3c.0.12	3c	0	12	SA:B	0	BSAS	7200	2538546/5198943744
data	3c.0.13	3c	0	13	SA:B	0	BSAS	7200	2538546/5198943744
data	3c.0.14	3c	0	14	SA:B	0	BSAS	7200	2538546/5198943744

Referring to the Information shown in the exhibit, what is the source of the problem?

- A. The vldb database is offline.
- B. The aggregate aggr2 has a failed disk.
- C. The databases on Node03 must be switched from secondary to master.
- D. The broken disk in Node03 is the source of the problem.

Answer: D

Explanation:

The broken disk in Node03 is causing the cluster ring to be offline, which prevents the CIFS SVM from being accessible. The cluster ring is a distributed database that stores cluster configuration information and enables communication between cluster nodes. If the cluster ring is offline, the cluster cannot function properly and the CIFS SVM cannot serve data to clients. The other options are not relevant to the CIFS SVM connectivity issue. Reference = <https://www.netapp.com/support-and-training/netapp-learning-services/certifications/support-engineer/>
<https://mysupport.netapp.com/site/docs-and-kb>

Question: 4

You have a customer who is concerned with high CPU and disk utilization on their SnapMirror destination system. They are worried about high CPU and disk usage without any user operations. In this situation, what should you tell the customer?

- A. Suggest that the customer manually cancel any scanners on the destination to reduce CPU usage.
- B. Explain that background tasks such as SnapMirror throttle up in the absence of user workload.
- C. Suggest that the customer throttle their SnapMirror relationships to reduce resource consumption.
- D. Explain that only user workload should use the CPU and Investigate further.

Answer: B

Explanation:

[SnapMirror is a data replication technology that allows efficient and flexible data protection and disaster recovery for NetApp ONTAP storage systems1](#)

SnapMirror transfers data between source and destination volumes using a network connection. [SnapMirror can use storage efficiency features such as compression and deduplication to reduce the amount of data transferred and stored1](#)

SnapMirror transfers are scheduled and controlled by policies that define the frequency, retention, and priority of the transfers. [SnapMirror policies can also specify the network bandwidth limit for the transfers2](#)

SnapMirror transfers are considered background tasks that run in the absence of user workload. [SnapMirror transfers can consume CPU and disk resources on both source and destination systems, depending on the amount and type of data being replicated3](#)

SnapMirror transfers can throttle up or down depending on the availability of system resources and network bandwidth. SnapMirror transfers will throttle up when there is no user workload, and throttle down when there is user workload. [This is to ensure that SnapMirror transfers do not impact the performance of user operations3](#)

Therefore, if a customer is concerned with high CPU and disk utilization on their SnapMirror destination system, the best answer is to explain that background tasks such as SnapMirror throttle up in the absence of user workload. [This is normal and expected behavior, and it does not indicate a problem with the system3](#)

Reference:

[1: ONTAP 9 Data Protection - SnapMirror - The Open Group](#) [2: ONTAP 9 Data Protection - SnapMirror Policies - The Open Group](#) [3: SnapMirror storage efficiency configurations and behavior - Resolution Guide - NetApp Knowledge Base](#)

Question: 5

You are attempting to connect a NetApp ONTAP cluster to a very complex network that requires LIFs to fail over across subnets.

How would you accomplish this task?

- A. Configure an equal number of UFs on each subnet.
- B. Configure VIP LIFs using OSPF.
- C. Configure VIP LIFs using RGP.

<https://www.examsnest.com>

D. Configure a LIF failover policy for each subnet inside a single broadcast domain.

Answer: C

Explanation:

[A LIF \(Logical Interface\) is a logical entity that represents a network connection point on a node¹.](#)

[A VIP LIF \(Virtual IP LIF\) is a LIF that can fail over across subnets within an IPspace².](#)

[BGP \(Border Gateway Protocol\) is a routing protocol that enables VIP LIFs to advertise their IP addresses to external routers and to update the routing tables when a failover occurs³.](#)

[To connect a NetApp ONTAP cluster to a complex network that requires LIFs to fail over across subnets, you need to configure VIP LIFs using BGP on the cluster and on the external routers³.](#)

[This way, you can ensure that the network traffic is routed to the optimal node and port for each VIP LIF, and that the network connectivity is maintained in the event of a node or port failure³.](#) Reference:

[1: Logical Interfaces, ONTAP 9 Documentation Center](#)

[2: VIP LIFs, ONTAP 9 Documentation Center](#)

[3: Configuring BGP on a cluster, ONTAP 9 Documentation Center](#)



ExamsNest

Your Ultimate Exam Preparation Hub

Thank You for trying the PDF Demo

Vendor: NetApp

Code: NS0-593

Exam: NetApp certified support engineer - ONTAP specialist

<https://www.examsnest.com/exam/ns0-593/>

Use Coupon “**SAVE15**” for extra 15% discount on the purchase of Practice Test Software. Test your Exam preparation with actual exam questions.

Start Your Preparation